

58VMR Performance™ 80

Variable Speed 4-Way Multipoise Furnace



58VMR Variable Speed 4-Way Multipoise Furnaces

The model 58VMR Oil-Fired Furnace is a variable speed multipoise-style unit designed for upflow, downflow, or horizontal applications. The model 58VMR is available in 2 sizes. Each size can be fired at 3 different rates by a simple nozzle change. Unit 58VMR105 covers input ranges from 70,000 to 105,000 Btuh. Unit 58VMR120 covers input ranges from 120,000 to 154,000 Btuh.

Its unique silencer baffle reduces combustion noise for quieter operation. Model 58VMR is UL, ULC, and GAMA certified at 83.5% AFUE for multipoise applications. The design of this furnace is such that a Carrier air conditioner, heat pump, humidifier, or electronic air cleaner can easily be added for a complete home comfort system.

- Stainless steel combustion chamber/primary heat exchanger
- Variable speed, ECM blower motor
- Continuous fan switch
- Enclosure for burner and controls
- Riello burner
- GE fan controls
- Access door to blower compartment
- Eligible for consumer financing through the Retail Credit Program
- Fully welded secondary heat exchanger
- Flue silencer baffle for noise reduction
- External side mount filter rack for upflow
- Higher pump pressure for better performance